



Product Code: BTJ102550TA

Air Hydraulic

Jack ruck.

3-Stage 10,000kg 25,000kg 50,000kg

The BTJ102550TA quickly and easily manages a hefty 50,000kg in the first stage lift position, 25,000kg at the higher 2nd stage extension and 10,000kg at its highest 3rd extension. This Air Actuated Commercial Jack is designed for heavy duty commercial use and features a long reach "T" handle and large rubber wheels for smooth manoeuvring around the workshop. With a low-profile minimum height of 160mm this jack is ideal for low ground-clearance vehicles and a high lift maximum of 472mm (includes additional lifting saddles), this BORUM Air Actuated Jack is a very versatile heavy-lifter suitable for most workshops.



Double Sealing Function using XTP Industry Sealing Telescopic air actuation lift (air-hydraulic pump) Long T-handle easily positions jack under vehicle Self-Returning Lowering and Lifting Switch Internal and External Cylinders hard chromed High manoeuvrability & deep reach under vehicles 2 extension adaptors / saddle plates

Large rubber wheels

All adaptors can be properly stored for transport on each side of the jack

Industrial

Specifications

First Stage: 50,000kg Safe Working Capacity Second Stage: 25,000kg Safe Working Capacity Third Stage: 10,000kg Safe Working Capacity

First Stage Hydraulic Lift: 61mm Second Stage Hydraulic Lift: 61mm Third Stage Hydraulic Lift: 69mm

Minimum Height: 160mm Maximum Height: 471mm Adaptors: 45mm and 75mm Handle Length: 1370mm

Operating Air Pressure: 145-175psi

Chassis: 825x282x160mm

Nett Weight: 61kg



Quality since