



Product Code: BTJ204060TA

Air Hydraulic

Truck Jack

3-Stage 20,000kg 40,000kg 60,000kg

The BTJ204060TA quickly and easily manages a hefty 60,000kg in the first stage lift position, 40,000kg at the higher 2nd stage extension and 20,000kg at its highest 3rd extension. This Air Actuated Commercial Jack is designed for heavy duty commercial use and features a long reach "T" handle and large rubber wheels for smooth manoeuvring around the workshop. With a low-profile minimum height of 150mm this jack is ideal for low ground-clearance vehicles and a high lift maximum of 447mm (includes additional lifting saddles), this BORUM Air Actuated Jack is a very versatile heavy-lifter suitable for most workshops.



Double Sealing Function using XTP Industry Sealing Telescopic air actuation lift (air-hydraulic pump)
Long T-handle easily positions jack under vehicle Self-Returning Lowering and Lifting Switch Internal and External Cylinders hard chromed High manoeuvrability & deep reach under vehicles 2 extension adaptors / saddle plates
Large rubber wheels

All adaptors can be properly stored for transport on each side of the jack

INDUSTRIAL QUALITY

Specifications

First Stage: 60,000kg Safe Working Capacity Second Stage: 40,000kg Safe Working Capacity Third Stage: 20,000kg Safe Working Capacity

First Stage Hydraulic Lift: 57mm Second Stage Hydraulic Lift: 59mm Third Stage Hydraulic Lift: 61mm

Minimum Height: 150mm Maximum Height: 447mm Adaptors: 45mm and 75mm Handle Length: 1380mm

Operating Air Pressure: 145-175psi

Chassis: 875x295x150mm

Nett Weight: 67kg



Superior Quality since

1984